



# VERTI-DRAIN

0  
2  
1  
1



The Mustang 7120 aerates hard compacted soils at depths up to 8". With its large working width of 80" and fast operating speed, it is aimed at professionals managing large open spaces that seek maximum operational efficiency.



# VERTI-DRAIN 7120



Verti-Drains adjustable parallelogram design shatters the soil, and also allows for clean Coring, on all models.

- Heavy Duty
- Depths up to 8"
- Large working width of 80"
- Fast operating speed
- 1/2" or 3/4" shank tines



## WORKING SPECIFICATIONS

Working width	80" (2.00m)
Total width	84" (2.15m)
Weight	2,000lb (915 kg)
No. of tine arms	10
Working depth:	8" (200mm)
Speed productivity	1.00mph (1.61kph) @ 2 1/8" (55mm) spacing 34,649 sq ft/hr (3,220 sqm/hr) 1.18mph (1.90kph) @ 2.5" (65mm) spacing 40,949 sqft/hr (3,806 sq m/hr) 1.64mph (2.63kph) @ 3.5" (90mm) spacing 56,698 sq ft/hr (5,269 sqm/hr) 2.31mph (3.72kph) @ 5.0" (127mm) spacing 80,008 sq ft/hr (7,436 sqm/hr) 3.46mph (5.56kph) @ 7.5" (190mm) spacing 119,696 sq ft/hr (11,124 sqm/hr)
Tractor required:	45HP, lift cap, 2,200 lb (1000kg)

## FEATURES / BENEFITS

FEATURE	BENEFIT
Speeds over 3 mph	Fastest rate ever
Unique adjustable parallelogram forced heave	Shatters compaction in any ground conditions. Versatile with single-point adjustment for optimum results and hollow coring
Sealed bearings not bushings	Long maintenance free life
Simple tine design	Easy to change and cheap to replace
Solid and hollow tines	Versatile
80" working width	Quicker to finish

### CALL FOR YOUR FREE DEMO TODAY!

The market leading range of Verti-Drains have outsold and outperformed all competitors for the past twenty years. With a model to suit virtually every application, it's the widest range available anywhere.

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office toll free at 800-597-5664.



**Redexim Charterhouse Inc.**  
 950 Sathers Drive  
 Pittston Township, PA 18640, USA  
 Tel: 570-602-3058  
 Fax: 570-602-3060  
 www.redexim.com  
 E-mail: redexim@aol.com