



VERTI-DRAIN

6
2
5
7



The Verti-Drain 75 Series incorporates all the innovative technology of the second generation Verti-Drain line. This makes it the first choice for anyone looking for a full 16" deep penetration and high productivity up to 61,400 sq ft/hr. Available with a three-speed gearbox that will match up to any tractor.

The Verti-Drain 7526 comes into its own in large open spaces, which includes fairways, as well as, football, soccer and baseball fields. The standard 3/4" diameter 12" long solid tines can be replaced with a variety of solid or hollow tines.

VERTI-DRAIN 7526



Verti-Drains adjustable parallelogram design shatters the soil, and also allows for clean Coring, on all models.

- Features a central quick adjustment lever for easy adjustment of tine angle.
- For customers wishing to transport their Vert-Drain 75 series on highways, a retro fit hydraulic wheel system is available.
- All models are supplied with a rear roller, which acts as a storage stand.



WORKING SPECIFICATIONS

Working width	104" (2.60 m)
Working depth	Up to 16" (400 mm)
Tractor speed@500 rpm at PTO	
Spacing 2 1/2" (65 mm)	Up to 0.45 mph (0.70 km/h)
Spacing 5" (130 mm)	Up to 0.90 mph (1.40 km/h)
Spacing 7 1/2" (195 mm)	Up to 1.35 mph (2.10 km/h)
PTO speed: (max)	Up to 500 rpm
Weight	3,510 lbs (1,595 Kg)
Hole spacing side-to-side	5" (129 mm) @ 1" (24 mm) holes 2.5" (65 mm) @ 1/2" (12 mm) holes
Hole spacing in driving direction	2" - 7 1/2" (50 mm - 195 mm)
Recommended tractor size	7526 - 65 HP with lift cap of minimum 4,200 lbs (1,900 Kg) 7526H - 55 HP
Capacity (maximum)	
Spacing 2 1/2" (65 mm)	Up to 20,457 sq. ft (1,901 sq m)/ hour
Spacing 5" (130 mm)	Up to 40,915 sq. ft (3,803 sq m)/ hour
Spacing 7 1/2" (195 mm)	Up to 61,372 sq. ft (5,704 sq m)/ hour
Shipping dimensions	111" x 40" x 60" (2,780 mm x 1,000 mm x 1,500 mm)
Maximum tine size	Solid 1" x 16" (24 mm x 400 mm) Hollow 1 1/4" x 12" (32 mm x 300 mm)
Slip clutch setting PTO	Maximum 7,080 lb.inch (800 Nm)
Three point linkage	3- point CAT 2
Transmission oil	Life time grease EP 00
Lubrication grease	EP 2
Standard items	Set solid tines to 3/4" x 12" (19mm x 300mm) Front and rear roller 3- shuttle gearbox PTO shaft

FEATURES / BENEFITS

FEATURE	BENEFIT
Heavy weight	Deeper penetration
Slip clutch	Prevents damage to machine and tractor
16" (400 mm) penetration	Relief of compaction at depths no other machine can reach, removing any hard pan at depths up to 16" (400 mm)
Versatile applications	Football, soccer and baseball fields, golf courses and race courses

CALL FOR YOUR FREE DEMO TODAY!

The market leading range of Verti-Drains have outsold and outperformed all competitors for the past twenty years. With a model to suit virtually every application, it's the widest range available anywhere.

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office toll free at 800-597-5664.



Redexim Charterhouse Inc.
950 Sathers Drive
Pittston Township, PA 18640, USA
Tel: 570-602-3058
Fax: 570-602-3060
www.redexim.com
E-mail: redexim@aol.com