

## MULTI-SPIKE













For general aeration, the standard 1/8" (3mm) thick triangular knife will give you 8" (200mm) deep slits at a close 6" (150mm) spacing, while the fine slitting drum will give you 4" (100mm) deep slits at an extra close 3" (75mm) spacing.

For maximum penetration, even in hard ground, we recommend the optional hydraulic weight system.

## MULTI-SPIKE 1200

**Deep penetration** - Improves drainage and opens up the turf in both winter and summer programs

Fast operation - Covers large areas rapidly leaving a quality finish

**5 optional types of knives -** truckster, deep slitting, twist, fine slitting, coring spoon

Optional Wheel Kit- for tow-behind operation.

**Weight options** - hydraulic or static weights. Enables the user to obtain the most from his tractor and achieve maximum penetration



WORKING SPECIFICATIONS	Working width	56" (1,350 mm)
	Working depth	Up to 10" (250 mm)
	Weight	880 lbs (400 Kg)
	Hole spacing side-to-side	3" (75 mm), with fine slit knives 6" (150 mm), with all other knives/tines
	Hole spacing in drive direction, at maximum depth center-to center	With 3 knives per disk: 18" (440 mm) With 4 knives per disk: 13" (330 mm) With 6 knives per disk: 9" (220 mm) With 12 knives per disk: 4 ½" (110 mm)
	Recommended minimum tractor size	18 HP with lift capacity of minimum 1,100 lbs (500 Kg), or 12HP for towed version
	Capacity: At 5 km/hour (3.1mph) At 10km/hour (6.2mph) At 15km/hour (9.4 mph)	72,656 sq ft (6,750 sq m)/hour 145,313 sq ft (13,500 sq m)/hour 217,969 sq ft (20,250sq m)/hour
	Shipping dimensions	59" x 22" x 66" (1,480 mm x 550 mm x 1,640 mm) L x W x H
	Three point linkage	3- point CAT 1 & 2
	Lubrication grease	EP 2
	Standard items	Rear roller assembly Manual Support jack
	Optional tine kits:	truckster knife, twist knife, deep knife, fine slit knife, coring spoon

FITS	FEATURE	BENEFIT
FEATURES / BENEFITS	Rear roller	Smooth and clean finish
	Weight transfer options	Hydraulic system or static weights guarantee full penetration.
	2 optional prime movers	Tractors or trucksters.
	Solid construction	For a long active life

## CALL FOR YOUR FREE DEMO TODAY!

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office toll free at 800-597-5664.



Redexim Charterhouse Inc. 950 Sathers Drive Pittston Township, PA 18640, USA Tel: 570-602-3058 Fax: 570-602-3060 www.redexim.com E-mail: redexim@aol.com