

ProSeeder

New Seeders





The ProSeeder range of seeders quickly and accurately sow the seed into the seedbed. They work under all kinds of conditions, ensuring the ideal environment for the seed to germinate. The delivery rate of the seed is accurately adjustable for every kind of seed.



For the professional contractor whom needs a high capacity machine, that spreads accurately and can work under all conditions.



A fully adjustable forward harrow loosens any compaction made by the tractor tracks. This is followed by a heavy duty-leveling frame, ensuring the creation of a neatly finished seedbed.

The seeder moves on 2 heavy crushing rollers of different diameters, which will secure a well-prepared surface and a good soil contact of the seed. Between the two rollers a spring loaded harrow rakes the soil loose, while the seed is dropping. After the crushing action of the rear roller, the seedbed is left completely even and porous, creating the ideal environment for a quick establishment and germination of the seed.

The TP1500 is a simple, easy to use seeder that mounts quickly to most small compact tractors. It is a simplified version of the TP1700, without the leveling frame, and working with only one heavy crushing roller.



ProSeeder Working Specifications

Model ProSeeder	HP600	TP 1500	TP1700
Working Width	60 cms	150 cms	170 cms
Weight	35 kg	225 kg	450 kg
Hopper Capacity	15 kg	50 kg	100 kg
Tractor required	self-propelled	20 hp	30 hp
Capacity	400-500 m ² /h	$4000 \text{ m}^2/\text{h}$	5000 m²/h

Designed for small or inaccessible areas, especially on golf courses. The HP600 moves on two independent driving rollers, which will not disturb the soil while turning. The rollers crush the soil particulars and work the seed into the soil.



