

## EASYSPREAD







The new hydraulic powered Easy Spread provides all the benefits of its predecessor like the unique Easy Spread one-man operation. This machine can load itself and can spread up to 80 tons a day without the operator leaving the cab.

Without a doubt, the Easy Spread is the perfect, low cost solution to what was a most back-breaking task, making it an ideal machine for all sportsgrounds.

## EASYSPREAD 1300/1600

The Easy Spread can also be used for spreading salt on pathways in the winter. The hydraulically driven feed drum gives the operator greater control.

The Easy Spread can be adjusted from thick top dressing to light without leaving the tractor seat.

Loading is made easy with Easy Spread's hydraulically operated tilt



	Model	1300	1600
WORKING SPECIFICATIONS	Length	31" (0.78 m)	31" (0.78 m)
	Road Width	56.25" (1.43 m)	68" (1.72 m)
	Working Width	51" (1.30 m)	62" (1.60 m)
	Height	47" (1.20 m)	47" (1.20 m)
	Weight	585 lbs (265 kg)	713 lbs (323 kg)
	Capacity	17.6 cu ft (0.5 cu m)	26.5 cu ft (0.8 cu m)
	Hydraulics	Double acting	Double acting
	Minimum HP	28 hp w/2,200lb (1,000kg) lift cap	38 hp w/2,200lb (1,000kg) lift cap
	Linkage	Cat 1, 3-point hitch	Cat 1, 3-point hitch
	Delivery Rates	Dusting to 3/8" (10 mm)	Dusting to 3/8" (10 mm)
	Delivery Control	Hydraulic metering valve	Hydraulic metering valve
	Hydraulics  Minimum HP  Linkage  Delivery Rates	Double acting  28 hp w/2,200lb (1,000kg) lift cap  Cat 1, 3-point hitch  Dusting to 3//8" (10 mm)	Double acting  38 hp w/2,200lb (1,000kg) lift of Cat 1, 3-point hitch  Dusting to 3/6" (10 mm)

	FEATURE	BENEFIT	
FEATURES / BENEFITS	One man operation	A simple hydraulic control operated from the tractor cab engages the distribution drum and opens the gate to its preset stop	
	Self loading	Continuous and effective work flow results in reduced costs	
	Large spread amount	80 tons per day	
	Varied top dressings	Spreads any granular material, even salt for frozen pathways	
	Variable spread	Easy control of spread thickness from a light dusting to over 3/8" (10 mm)	

## CALL FOR YOUR FREE DEMO TODAY!

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office toll free at 800-597-5664.



Redexim Charterhouse Inc. 950 Sathers Drive Pittston Township, PA 18640, USA Tel: 570-602-3058 Fax: 570-602-3060 www.redexim.com F-mail: redexim@aol.com